



IMPACT AR PCC TRIGGER INSTALLATION INSTRUCTIONS

Thank you for purchasing this Timney Trigger. It has been designed and manufactured to provide you with a lifetime of dependable service. Each trigger is hand tested and calibrated on a rifle action before leaving our factory. Please read these instructions fully before you begin installing the trigger, you will be glad you did.

TOOLS NEEDED



Straight Punch



5/64" Hex key



or



Flat head or hex key to remove pistol grip

TIMNEY TRIGGER GUARANTEE

Material and workmanship: This Timney trigger has been carefully inspected, tested and adjusted to give a lifetime of dependable service. Every possible care has been exercised in its design and construction. If any defect in workmanship or material should develop under conditions of normal use and service, any necessary repairs, including parts and labor will be made at NO CHARGE to the purchaser providing that our inspection reveals parts were not damaged through accident, alteration, misuse, abuse or other causes beyond our control. We neither assume nor imply any oral or statutory warranties, and we neither assume nor authorize any person to assume for us any obligation or liability in connection with this trigger. Repairs or disassembly of this trigger in any manner without specific authorization, voids the guarantee.

**IF YOU HAVE TROUBLE CHECK OUT TROUBLESHOOTING STEPS ON
WWW.TIMNEYTRIGGERS.COM OR CONTACT US**

Need help with your install? Contact our customer service team via phone or email for assistance.

Phone: 623-223-1111 Fax: 623-223-1112 Support: technicalsupport@timneyusa.com

INSTALLATION INSTRUCTIONS

1 Before beginning work on any firearm make sure to remove the ammunition source and double check to ensure the chamber is empty.

2 To separate the upper and lower receiver, press out the two takedown pins.

3 Inside the pistol grip there is a large screw that will need to be removed using either a hex key or flathead screwdriver. When removing the pistol grip, **be careful not to lose the safety spring and plunger.**

4 Remove safety selector.

5 Use a straight punch to push out the pins that are holding the stock trigger assembly in place, then remove the stock trigger.

6 Now you're ready to insert your new Timney Impact PCC Trigger in the lower receiver! Drop in the trigger, reinstall the safety selector, and then insert trigger pins.

NOTE: For Aero Precision EPC9 installation: Before dropping in the trigger, first remove the two button screws attached to the bridge on the back of the trigger. Continue installation with bridge attached to the housing then follow the rest of step 6.

7 Tighten the pre-installed setscrews in the trigger housing located to the sides of each hammer spring leg.

8 Reinstall the safety detent, safety spring and pistol grip.

9 Reinstall the upper receiver on the lower receiver.

10 Perform a function check and enjoy your new Timney Trigger.



IF YOU HAVE TROUBLE CHECK OUT TROUBLESHOOTING STEPS ON WWW.TIMNEYTRIGGERS.COM OR CONTACT US

Need help with your install? Contact our customer service team via phone or email for assistance.

Phone: 623-223-1111 Fax: 623-223-1112 Support: technicalsupport@timneyusa.com

